

EPSON Professional Media

Somerset® Velvet for Epson

For use with

EPSON Stylus® Pro 7000EPSON Stylus Pro 9500EPSON Stylus Pro 7500EPSON Stylus Pro 9600¹EPSON Stylus Pro 7600¹EPSON Stylus Pro 10000²


EPSON Stylus Pro 9000

Product Information

Somerset has always been the first paper choice among serious artists and printmakers. Ever since the 1700s and the days of handmade paper, Somerset has enjoyed a reputation for quality that has continued to grow through the years. Now Epson brings you this old world paper, with an ink jet coating, to meet the quality requirements of the most demanding printmaker. Somerset Velvet for Epson is a 100% cotton, acid-free paper that delivers long-lasting prints when printed with EPSON Archival™ or UltraChrome™ Ink.

Like all of Epson's innovative media, Somerset Velvet is engineered to give you the highest resolution and color saturation possible. Epson's printer driver software actually optimizes the amount of ink released onto the page, based on the type of paper used. As always, EPSON supplies guarantee EPSON guality.

- 1 Photographic dye version and UltraChrome ink version
- 2 Photographic dye version and archival ink version



Features/Benefits

- Acid free to preserve fine art and photos
- 100% cotton rag for long term durability
- Radiant white surface for vivid color reproduction
- · Rich black images for prints with exceptional contrast
- Velvet surface for rich details and accurate reproduction
- 505 g/m2 basis weight for museum quality appearance (sheets)
- 255 g/m2 basis weight on rolls for versatility
- Enhanced 1440 dpi printing for high-quality output
- Dries instantly for easy handling with Epson inks

Feature Checklist

Feature	Performance	Additional Comments
Indoor/outdoor usage	Indoor only	
Lightfastness	Over 100 years EPSON Archival Ink Over 50 years UltraChrome Ink 5 years Photographic Dye Ink	Lightfastness ratings are based on accelerated testing of prints on specialty media, displayed indoors, under glass. Lightfastness only estimates the life of the ink, not the media
Archivability	Excellent	Buffered cotton base ensures archivability.
Resistance to water	Good	Bleeding does occur with incidental water contact. However, try to prevent exposure to moisture.
Ink drying	Immediate (less than 30 seconds)	Ink is dry to the touch after printing. However, it takes 24 hours before it cures and becomes durable.
Handling	Use gloves	Use gloves when handling the paper to avoid smudges and fingerprints on the printing surface.
Mounting	Recommended	Use rag board or other high quality, acid free mounting materials.
Lamination	Not recommended	if a protective coating is desired, use a fast-drying, acrylic spray with a UV absorbent.

NOTE: Actual print stability and longevity will vary according to image, display conditions, light intensity, humidity, atmospheric conditions, and post-printing treatments. Epson does not guarantee stability or longevity. For maximum print life, display all prints under glass or lamination or properly store them.

EPSON Professional Media Somerset Velvet for Epson

Technical Specifications	Rolls	Sheets
Basis weight	255 g/m²	505 g/m ²
Thickness	19 mil	36 mil
ISO brightness	96%	96%
Opacity	95%	99%
Hot lamination	No	No
Base material	100% Cotton rag	100% Cotton rag
Surface finish	Velvet	Velvet
Core size	3"	N/A
Spindle	3" high-tension ¹	N/A

¹ Optional printer accessory, available from Epson EPSON Stylus Pro 9500, Part No. C811052 EPSON Stylus Pro 7500, Part No. C811103

Driver Settings (Roll)

Printer	Driver
EPSON Stylus Pro 7600/9600	Enhanced Matte Paper
EPSON Stylus Pro 7500/9500/10000	Premium Luster Photo Paper

Driver Settings (Sheet)

Printer	Driver
EPSON Stylus Pro 7600/9600	Enhanced Matte Posterboard
EPSON Stylus Pro 7500/9500/10000	Premium Luster Photo Paper

Operating Specifications

Required temperature for optimum performance	60° - 80° F
	15° - 25° C
Required humidity for optimum performance	40% - 60% RH

(Note: High humidity will prolong the drying time for lamination purposes.)

Ordering Specifications (Individual Boxes)

Product Code	Product	UPC Code
SP91203	24" x 50' roll	0-10343-84410-0
SP91204	44" x 50' roll	0-10343-84411-7
SP91200	24" x 30'/20 sheets	0-10343-84406-3
SP91200-S	24" x 36"/3 sheets	0-10343-84407-0
SP91201	36" x 44"/10 sheets	0-10343-84408-7
SP91202	44" x 60"/10 sheets	0-10343-84409-4

Packaging Specifications (Individual Boxes)

Product Code	Dimensions (L x W x H)	Weight
SP91200	27.2" x 33.3" x 1.9"	12.5 lb
SP91200-S	27.2" x 33.3" x 1.9"	3.5 lb
SP91201	39.2" x 47.3" x 1.9"	25.0 lb
SP91202	44.5" x 62.5" x 1.5"	21.0 lb
SP91203	26.0" x 6.5" x 6.5"	6.5 lb
SP91204	46.5" x 6.5" x 6.5"	12.0 lb

MSRP

Product Code	Product	Cost
SP91200	24" x 30"/20 sheets	\$299.99
SP91200-S	24" x 30"/3 sheets	59.00
SP91201	36" x 44"/10 sheets	335.00
SP91202	44" x 50'	565.00
SP91203	24" x 50'	169.00
SP91204	44" x 60"/10 sheets	299.00





Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd. 3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5

Epson Latin America

6303 Blue Lagoon Drive, Miami, FL 33126

Specifications are subject to change without notice. EPSON and EPSON Stylus are registered trademarks of Seiko Epson Corporation. UltraChrome, EPSON Archival and EPSON Photographic Dye are trademarks of Epson America, Inc. Somerset is a registered trademark of Inveresk PLC. All other products and brand names are registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2002 Epson America, Inc. CPD-13833 5K 6/02 CL Printed on Recycled Paper

