

# The Art of Expression since 1584

The Hahnemühle Digital FineArt Collection



## Photo Rag® Duo, 316 g/m<sup>2</sup>

White, 100% rag content, smooth surface, double-side coated

© Milton H. Greene Archives "Dovima", 2002 - www.archivesmhg.com

### Product Description

This paper has the same qualities as the standard Photo Rag®, but the double sided coating makes it ideal for applications such as book making and photo albums.

### Applications and Characteristics

The coated side of this paper provides excellent image sharpness and optimum colour graduation. The coating also offers a very high level of water resistance.

Common applications include:

Photographic and fine art reproduction, business cards, greeting cards, certificates and bookmaking. It is also ideal for computer generated artwork.

### Physical Characteristics

	Unity	Valuation	Test Norm / Notes
Test Conditions		23°C / 50% R.H.	CSS22
Weight total	g/m <sup>2</sup>	316	EN ISO 536
Thickness	mm	0,50	EN 20534
Whiteness	%	92,5	ISO 11475 (W <sub>cie</sub> / D65, 2°)
Opacity	%	99,0	ISO 2471
Media Colour		bright white	not bleached
pH-Value total		8,1	DIN 53124
Water resistance		very high	
Cobb		85,0	EN 20 535
Ink limit	%	245	
Special features	coated both sides		

All indicated data to be understood as typical average values.

### Conditions of use and storage

Use and store at a relative humidity of 35 to 65% and a temperature of 10 to 30° C (50° – 86°F).

All recommendations and product indications are for your guidance, and are subject to our test criteria, these remain subject to change without prior notice. There is no guarantee that the same results can be consistent.

Use care in handling printed material, surface susceptible to abrasion.

Store papers in archive quality envelopes, folders, and boxes.

Use only archive grade tapes and glues for mounting & framing.