



MonacoOPTIX^{XR}

Precision calibration
for LCD and CRT
displays



Complete Solution for Accurate Monitor Profiling

Creative professionals rely on the ability to view images accurately on their monitors. A calibrated and profiled display ensures accurate and consistent color throughout the digital workflow.

MonacoOPTIX^{XR} is a monitor calibration system that combines a state-of-the-art colorimeter with powerful and easy-to-use software to provide an outstanding profiling solution for both LCD and CRT displays. Attach the sensor and the wizard-like interface prompts the user through the profiling process, creating a monitor profile in just a few minutes!

Now Available in Two Editions

MonacoOPTIX^{XR}

A robust monitor profiling package for photographers, graphic artists and creative professionals. Includes a site license.

MonacoOPTIX^{XR}PRO

The professional package for workgroup situations, customers who demand expert levels of control, flexibility and the highest quality profiles.



The MonacoOPTIX^{XR} device offers unparalleled quality with X-Rite precision. Architected with state-of-the-art filter technology for unrivalled profiling accuracy.

How it works:

Step 1: Install the MonacoOPTIX^{XR} software on your computer.

Step 2: To profile your display, attach the weight to the cable so it counter-balances the sensor. Plug the USB cable into the port on your computer.

Step 3: Launch the MonacoOPTIX^{XR} software. The wizard-like interface will guide you through the process of creating and saving a monitor profile.

Step 4: The profile will be saved in the appropriate system directory, and will become the default profile for your monitor.

Feature	Benefit	Monaco OPTIX ^{XR}	Monaco OPTIX ^{XR} PRO
Create ICC profiles for CRT and flat panel displays	Use the same device for all your displays	✓	✓
Customizable white point for accuracy	Use presets, user-defined values or measure ambient light with your instrument	✓	✓
Set hardware white point with measurement device, if monitor has adjustable RGB controls	Obtain greatest accuracy with instrument-assisted measurement	✓	✓
Hardware-assisted brightness and contrast adjustment	Ensure the widest tonal range and largest color gamut possible for your display	✓	✓
Adaptive brightness setting for flat panel displays	Provides accurate color in any viewing environment	✓	✓
Convenient workflow option to skip calibration procedure	Profile quickly when necessary	✓	✓
Profile reminder application	Establish a profiling schedule for your entire workgroup	✓	✓
Multiple monitor calibration	Calibrate multiple displays connected to the same workstation quickly and easily	✓	✓
Monitor profile validation	Check the accuracy of your profile. Find out-of-gamut colors		✓
Monitor drift trending	See how displays drift over time, and establish profiling schedules		✓
Workgroup display matching	Have multiple displays in a workgroup set to the same luminance values		✓
Calibration curve editing	Fine tune the color balance and white point of your display		✓
Advanced mode—on screen display (OSD) testing, black bias control and calibration to target values	Greater control for expert users		✓
Optional table-based profiling	Provides greater accuracy		✓

System Requirements

Macintosh OS X

- Power Macintosh or better
- Macintosh System 10.2 (Jaguar) or later
- 128 MB system RAM, 64 MB free disk space
- Color monitor with 24-bit or greater video card (with LUT support)

Windows 98SE/ME/2000/XP

- Pentium PC or better
- 32MB application RAM, 50MB free disk space
- Color Monitor with 24-bit or greater video card (with LUT support)
- Dual monitor support requires two (or more) separate video cards that support LUTs. Single video cards with dual monitor support are not supported on the Windows platform.



xrite.com

ISO 9001
Certified

X-RITE WORLD HEADQUARTERS
Grandville, Michigan USA
(616) 534-7663
(800) 248-9748
FAX (616) 534-8960

X-RITE LATIN AMERICA
Hollywood, Florida USA
954-927-4979
FAX 954-927-4979

X-RITE LTD.
Poynton, Cheshire
United Kingdom
44 (0) 1625 871100
FAX 44 (0) 1625 871444

X-RITE MÉDITERRANÉE
Massy, France
33 1-6953-6620
FAX 33 1-6953-0052

X-RITE ITALY S.R.L.
Origgio (VA), Italy
(39) 02-967-34266
FAX (39) 02-967-30681

X-RITE GmbH
Köln, Germany
(49) 2203-91450
FAX (49) 2203-914519

**X-RITE INTERNATIONAL
TRADING LIMITED**
Shanghai, PR China
86-21-6427-2426
FAX 86-21-6427-5816

X-RITE ASIA PACIFIC LTD.
Quarry Bay, Hong Kong
(852) 2-568-6283
FAX (852) 2-885-8610

X-RITE IBERICA
Barcelona, Spain
34 93 567 70 73
FAX 34 93 567 70 78

Vyskov, Czech Republic
(00) 420 517-320-331
FAX (00) 420 517-320-335

Tokyo, Japan
81-3-5439-5971
FAX 81-3-5439-5972

INFORMATION PROVIDED IN THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE. The user assumes the entire risk as to the accuracy and the use of this information. All text must be copied without modification and all pages must be included. All components of this information must be distributed together. This information may

not be distributed for profit. © X-Rite, Incorporated 2004. X-Rite® is a registered trademark of X-Rite, Incorporated. Other brand and product names are trademarks of their respective holders. All trademarks may be registered in the United States and/or other countries. Product design and specifications subject to change without notice.